

AMENDMENTS TO THE CLAIMS

The current listing of the claims replaces all previous amendments and listings of the claims.

1. (Currently Amended) A display apparatus ~~having~~ comprising:
an optical material between a pair of substrates, ~~and having~~
a plurality of display pixel sections, and
a spacer disposed between the pair of substrates, the spacer being fixed on at least one
of the substrates.

wherein each of the substrates has a glass substrate and a film that is attached to an outer surface of the glass substrate and has a thickness greater than a thickness of the glass substrate,

at least one of the films is formed of a polarizer plate, and
each of the glass substrate is formed to have a thickness that permits bending of the display apparatus.

2. (Original) The display apparatus according to claim 1, wherein the thickness of each of the glass substrates is 0.15 mm or less.

3. (Original) The display apparatus according to claim 2, wherein the display apparatus is formed to be bendable with a radius of curvature of 200 mm or less.

4. (Original) The display apparatus according to claim 1, wherein the optical material is a liquid crystal composition.

5. (Original) The display apparatus according to claim 1, wherein the optical material is an EL (electro-luminescence) material.

6. (Canceled)

7. (Original) The display apparatus according to claim 1, wherein each of the display pixel section includes a TFT (thin film transistor) and a pixel electrode, which are formed on one of the glass substrates.

8. (Original) The display apparatus according to claim 7, wherein the TFT includes a p-Si film (polysilicon film).

9.-19. (Canceled)

20. (Currently Amended) A display apparatus comprising:
a display panel configured to hold a liquid crystal layer between an array substrate and a counter substrate; ~~and~~
a backlight unit that illuminates the display panel[.]; and
a spacer disposed between the substrates, the spacer being fixed on at least one of the substrates,

wherein the array substrate includes[(:)]

a first light-transmissive insulation substrate[(:)],

a signal line and a scan line that are disposed to be substantially perpendicular to each other on one of major surfaces of the first light-transmissive insulation substrate[(:)],

a switch element disposed near an intersection of the signal line and the scan line[(:)], and

a pixel electrode connected to the switch element,

wherein the counter substrate includes[(:)]

a second light-transmissive insulation substrate[(:)], and

a counter electrode disposed on one of major surfaces of the second light-transmissive insulation substrate so as to face the pixel electrode, and

wherein polarizer plates are disposed respectively on the other major surfaces of the first light-transmissive insulation-substrate and the second light-transmissive insulation substrate, the polarizer plates having thicknesses greater than those of the first light-transmissive insulation substrate and the second light-transmissive insulation substrate.

21.-46. (Canceled)